



AB-88D

- Classic economy design
- Easy maintenance
- Multi data interface options available

PRODUCT FEATURES



Big paper roll loadable
80 mm diameter paper roll makes printing longer and stable.



Easy maintenance
Simple inner frame, module design, easy to maintain.



Multi data interface
Available of LAN / USB / RS232 ports.

SPECIFICATIONS

Printing Method	Direct Thermal	CODE PAGES SUPPORTED	PC437 / Katakana / PC850 / PC860 / PC863 / PC865 /
Resolution	8dots/mm		WPC1253 / Iran / WPC1256 / PC737 / WPC1250 /
Printing Density	640dots/line		WPC1252 / PC866 / PC852 / PC858 / Latvian / Vietnam /
Printing Speed	220mm/s		Uigur / WPC1255 Israel / WPC862 / WPC1257 /
Paper Width	72mm		WPC775 / WPC1251 / PC861 Icelandic / PC857 Turkey
Paper Type	Thermal Paper: 79.5±0.5mm Max Diameter: 80mm		/ PC874 Thai / PC3021 Bulgarian / User define
Tearing way	Auto cut	Supportable Barcode Types	JAN13(EAN13) / JAN8(EAN8) / CODE39 / CODE128 /
Sensor	Out of paper		UPC-A / UPC-E / ITF / CODABAR / CODE93
Character Size	ANK Character, Font A: 12x24, FontB: 9x17, Chinese: 24x24	Interface Options	USB+RS232,(WIFI or Bluetooth is optional)
Character Per Line	Font A: 42/48/53(EPSON Mode, adjusted via 8 DIP Switch) Font B: 56/64(Normal Mode)	Life	Printer Head:100,000,000 pulses or more,100 kilometers or more Cutter:1,000,000 cuts or more
Font Library	GBK big font library	Environmen	Work Temp. and Humidity: 0~50 C ;30~85%RH Environment Temp. and Humidity:-20~60 C ;30~85%RH
Buffer Capacity	20K	Adapter	DC24V,2.5A
Dimensiont	192.8(L)X145(W)X140.5(H)mm	Drawer Port	DC24V,1A(RJ11)
Carton Sizes	260mmX210mmX230mm inner box-80mm	Transport packing quantity	8
		Authentication information	CCC Certification / CB Certification / CE Certification / FC Ccertification

