

AB-342M

HIGHLIGHTS

- Easy Paper loading
- Faster printing speed up to 70-80mm/s
- Long time Lithium-ion battery
- Multi connection port: USB, RS-232, Bluetooth
- Mobile printer can work under many mobile devices.
- Wide usage: Outdoor fine, logistic system, wild quest record.
- With LCD Display



SPECIFICATIONS

Item	Parameter	Character Size	8x16, 16x16, 9x17, 12x24, 24x24
Printing	Direct thermal line printing	Barcode	JAN13(EAN13), JAN8(EAN8), CODE39, CODE93,
Resolution	203 DPI (8dot/mm)		CODE128, CODABAR, ITF, UPC-A, UPC-E
Paper supply method	Easy paper loading	QR Barcode	QR, PDF417
Print width	114mm	Image	Support
Characters per line	114mm paper: 69(12x24)/92(9x17)	Paper	Thermal paper roll, adhesive sticker thermal paper etc.
Printing speed	Thermal paper: 80m/s		(bill paper, label paper, black marked paper)
	Stick paper: 70mm/s	Paper width	114mm/110mm
Feeding speed	80mm/s	Paper diameter	≤60mm
Receive buffer size	128KB	Cutter type	Manual tearing
Memory	SRAM:8M FLASH:4M	Power input	Adaptor 9V/3A DC; 7.4V Lithium battery
Sensors	Black mark sensor, label gap sensor, paper	Printer head	100,000,000 pulses; Paper feed length >50km
	absence sensor, cover open sensor,	Battery	400 Cycles Rechargeable
	temperature sensor	Operating temperature	-20 to 50°C, 10%~90%RH
Interface	RS-232, USB2.0, Bluetooth 4.0 dual-mode	Storage temperature	-3 to 80°C, 5%~90%RH (without condensation)
Character set	ANK Character set, Simplified Chinese character	Dimensions	159(W) * 152(D) * 72(H)mm
	set (GB18030), Taiwan (BIG5) traditional Chinese	Weight	700g approx.

