

80mm Thermal printer

AB-T88



HIGHLIGHTS

- Fast and stable printing speed up to 200mm/s per second.
- Reliable auto-cutter up to 1 million cuts.
- Drop-in-paper loading
Wall mount bracket is for limited space.
- Full and partial cut.

Reference Applications



Hospitality & Leisure

Reducing transaction time is invaluable to any business in today's hospitality

- Point-of-sale receipting
- Coupon printing
- Kitchen printing
- Bar receipt printing
- Ticketing
- Electronic patient records
- document, records and case note tracking

PRODUCT FEATURES

Easy paper loading

Easy paper loading designing and support big size paper roll.



Easy paper loading

Hung on the wall


Convenient space-saving, The printer can be hung on the wall.



Hung on the wall

Four interface choice

Four interfaces option meets various working requirements.



Parallel Serial
USB 2.0 Ethernet

SPECIFICATIONS

AB-T88

Printing Method	Direct Thermal
Printing Speed	200mm/s
Resolution	203DPI (8dots/mm)
Character Set	Alphanumeric Character :95
Character Size	Font A: 12 X 24 Font B: 9 X 17
Character Per Line	48
Paper type	Thermal Paper
Paper Width	80 ± 0.5mm
Paper Roll Diameter	Max φ 80.0mm
Paper Supply Method	Easy Paper Loading
MCBF	100,000,000 Pulses
Auto cutter	1,000,000 cuts
Auto cutter	Partial Cut/Full Cut
Drawer Port	RJ 11
Emulation	ESC/POS
Interface options	RS-232C, IEEE1284, USB, Ethernet
Language	Buyer Language Support
Power Supply (Adapter)	Ac120 ~230V ± 10% DC 24V,2A
Dimensions (W*L*H)	148x 195 x 145 mm
Operating Temp	0 ~ 50 °C