

## ZQ-S2D16B



### HIGHLIGHTS

- Wireless 2D barcode scanner
- Build in RS232 and USB interface
- 1.5m Drop Resistance
- Ultra low error rate at 1/5,000,000

### Product Parameter

Model		ZQ-S2D16B	
Light Source	650nm VLD	Pitch,Skew	65°, 60°
Interface	USB, RS232	Depth of Field	20mm-90mm(4mil);30mm-400mm(12mil)
Working Distance	30m-50m	Revolve Angle	46°H×34°V
Communication	Bluetooth4.0	Dimensions	160mm×65mm×85mm(L×W×H)
Memory Capacity	256K	Weight	200g
Precision	≥4mil	Battery	3.7V 650mAh Lithium polymer battery
Error Rate	1/5million	Charging Period	About 2 hours
Print Contrast	≥25%	Input Voltage	DC 5V±5%
Scan Speed	25cm/s(MAX)	Current Working Current	230mA
Decode Capability	2D: PDF417, QR Code(Model 1/2),	Standby Current	7mA
	DataMatrix(ECC200, ECC000,050, 080, 100,140),Aztec, Maxicode, etc	Humidity	5% ~ 95%
		Operating Temperature	-10℃ ~ 50℃
		Storage Temperature	-40℃ ~ 80℃
	1D:Code128, EAN-13, EAN-8, Code39,	Dustproof and Waterproof	IP54
	UPC-A, UPC-E, Codabar, Interleaved 2 of 5,	ESD Protect	15KV
	ISBN, Code 93, UCC/EAN-128,	Drop Test	1.5m drops on the concrete surface
	GS1 Databar, etc.		