



Salient Features:

- Ultra-low error rate at 1/5,000,000
- Multiple data ports interface
- Dust proof & Water proof
- 2D barcode scanning

SPECIFICATIONS:

Interface	TTL-232, USB (HID-KBW, virtual serial port).
Optical system	CMOS
Resolution	640*480
Light Source	Lighting: White LED Focus: Red LED
Precision	≥4mil
Depth of field (Code/ depth of field/ density)	EAN-13 / 45mm-269mm / (13mil 13 bytes.)
	Code39 / 35mm-119mm / (5mil 7 bytes).
	Code128 / 43mm-310mm / (13mil10 bytes.)
	QR Code / 19mm-185mm / (15mil 30 bytes.)
	Data Marix / 45mm-116mm / (10mil30 bytes).
	PDF 417 / 40mm-105mm / (6.67mil 30 bytes.)
Reading mode	Manual trigger / automatic sensing
How to prompt	Buzzer (volume adjustable);
Read the angle	The corners are 360degrees, the elevate ± 55degrees, and the ± 55 degrees
Perspective	Horizontal 36degrees, vertical 27 degrees
Ambient light	Dark environment, indoor natural light
Decode Capability	1D barcodes: Code 128, Ean-13, Ean-8, UPC-E, UPC-A, ITF-25 (Interleaved 2 Of 5), Code39, Code93, Codabar
	2D Code: QR Code, Data Matrix, PDF417