

Features:

- Easy Portability
- Adjustable Strap
- Longlasting Battery
- Highly durable



Specification :

Light Source	Aiming:650nm Red LED, Illumination: White LED(265 lux@130nm)	
Indicator	Beep prompt; LED	
Communication	Bluetooth 3.0	
Distance	≤50M	
Resolution	≥5mil	
Image Sensor	648x480 CMOS	
Sensitivity	Roll 360°, pitch±55°, skew±55°	
Field of View	35°(H), 27°(V)	
Error Rate	1/5 million	
Print Contrast	≥20%	
Decoding Capability	1D: Code 128,EAN-13,EAN-8,UPC-E,UPC-A,ISBN,ISSN,Code11,ITF-25(Interleaved 2 of 5), Code39,Code93,Code32,Codabar,Matrix 2 of 5,Industrial 25,IATA 25,MSI Plessey, etc. 2D: QR Code, PDF417, Data Matrix, MicroQR Code, etc.	
Typical Depth of Field	EAN13	50mm - 250mm
	Code39	55mm - 120mm
	Code128	50mm - 260mm
	Data Matrix	25mm - 170mm
	PDF417	50mm - 110mm
Material	ABS+EVA	
Memory Capacity	512KB	
Input Voltage	DC 3.3V±5%	
Working Current	110mA(Working); 60mA(Standby)	
Operating Temperature	-20°C~60°C	
Storage Temperature	-40°C~80°C	
Humidity	5% ~ 95% (Non-condensing)	
Drop Resistance	1.5m drop to concrete	
Ambient lighting	0 ~ 100,000 lux	
Vibration	8 G r.m.s., from 10 to 500 Hz, 2 hours per axis, 3 axes	