



CUSTOMER POLE DISPLAY

ZQ-VFD2300

The customer display series is compatible with the Epson mode, with a three-level adjustable height. The power supply adapter is optional.

HIGHLIGHTS

- EPSON emulation compatible
- 3 level pole for length adjusting
- Adaptor of wide power input range for easy using

APPLICATION REFERENCE

Zonerich Customer Pole display is widely used in kind of POS Solutions:

- Hospitality solutions
- Retail Cashier Systems
- Car Parking Systems



SPECIFICATIONS

Display Method	Vacuum Fluorescent Display	COM Port	Baud rate from 2400BPS to 19200BPS (9600BPS as default)
Display Type	Two line dot matrix	Power	DC 12V, 1A
Language Supported	English	Power Consumption	<4W
Font	5x7 dots	Environment	Work Temp. and Humidity: -10~55°C, 35~85%RH
Characters	40 (20 x 2 Lines)		Storage Temp. and Humidity: -20~65°C, 10~85%RH
Character Set	96 ASCII	Height Supported	170mm, 170+120mm, 170+120+120mm
Emit Color	Green	Display Panel Sizes	225x95x62mm
Back Light	No	Display Base Sizes	220x110x75mm
Drive Mode	Dynamic	Package Sizes	280x240x125mm
Audio	No	Net Weight	0.8kg
Emulation	EPSON, Nortriake, futaba, PL-200, UTC Standard, ENHANCE, AEDEX, ADM788, DSP800, CD5220 (PTC), LOGIC, POST300, UTC, EMAX	Gross Weight	1.35kg
Elevation.	0~90°		
Ports	1 x RS232, 1 x USB, 1 x DC12V		