

## ZQ-S2D52 2D Scanning Platform

### Specifications

Item		Description
Illumination		White light LED
Interfaces		USB (HID-KBW、VCOM)、UART
Precision		≥5mil
Decode Capability	2D	PDF417、QR Code(Model 1/2, Micro)、Data Matrix (ECC200, ECC000, 050, 080, 100, 140)、Aztec Code
	1D	Code 128、EAN-13、EAN-8、Code 39、UPC-A、UPC-E、Codabar、Interleaved 2 of 5、Matrix 2 of 5、Standard 2 of 5、Codablock、MSI、Code 93、Code 11、Telepen、UCC/EAN-128、GS1 Databar、Plessey Code、RSS、Postnet
Scan Speed		25cm/s
Depth of Field	CODE39(5mil)	50mm-120mm
	UPC/EAN(13mil)	20mm - 320mm
	PDF 417 (10mil)	45mm - 200mm
	Data Matrix (10mil)	45mm - 200mm
	CODE39(20mil)	10mm - 400mm
Revolve Angle		45° H×30° V
Resolution		640x 480
Dimensions		95mm×87mm×162mm (L×W×H)
Weight		250g
Input Voltage		5V DC±5%
Current	Work Current	300mA
	Standby Current	40mA
Humidity		5% - 95%
Operating Temperature		-20℃ ~ 60℃
Storage Temperature		-30℃ ~ 70℃
Keyboard language		USA , UK , France , Germany , Italy , Russia
Drop Test		0.5m drops on the concrete surface
Vibration		8 G r.m.s., from 10 to 500 Hz, 2 hours per axis, 3 axes
Ambient Light		0 ~ 100,000 lux (natural light)

### Picture

