

Features

- Capacitive touch panel
- Perfect Retail Solution
- Optional Battery



Specification

CPU	Intel Bay-trail J1900 Quad Core	58mm Printer (Optional)	Printing method: Direct thermal Printing speed: Max.250mm/s Printing width: 48mm Paper width: 57.5±0.5mm Maximum outer diameter: 50m Cutter: Manual
Memory	4G; Optional:8G, 16G		
Storage	64G, optional 128G		
Network	Ethernet: RTL8168DE PCI-E NIC10/100/1000M adaptive		
Main Display	Dimension: 11.6 inch Resolution: 1920*1080	80mm Printer	Printing method: Direct thermal Resolution: 8 dots/mm Printing density: 640 dots/line Printing speed: Max.250mm/s Printing width: 72mm Paper width: 79.5±0.5mm Maximum outer diameter: 60mm Cutter: Auto-cutter Interface: USB
Touch screen	Dimension: 11.6 inch Type: Capacitive		
Voice prompt	Optional Built-in 2W speaker		
Customer display	LCD Support 20 characters per line, 2-line display Optional 11.6 Inch, 1920*1080, EDP		
Dimension	310x299.8x102.4mm (LxWxH)	Environment	Working temperature: -10℃-40℃ Storage temperature: -20℃-55℃ Humidity: 20%-90% RH
Power adapter	12V 4A		
		Optional module	NFC; Dallas Key; 5 inch customer display Battery: 24V rechargeable



Dallas key Optional



NFC Optional



5 inch display Optional



NFC Module