

ZQ-A1012

Features

- Compact and exquisite design;
- Wider viewing angle rotating display;
- Dual barcode readers optional and face recognition cameras;
- Various peripheral options
- Capacitive multi-points touch panel



Specifications

System	Android 7.1	Scanner module 2 (Optional)	Prompt mode: buzzer, LED indicator
CPU	Rockchip RK3368, Octa core, 1.5GHz; (RK3288 optional)		Trigger mode: command trigger, automatic induction trigger, continuous trigger
GPU	PowerVR G6110		Setting method: scan code setting, command setting
RAM	2G		Communication interface: USB HID keyboard
Storage	8G		Recognition angle: rotation 360°, left and right tilt ±45°, front and back tilt ±45°, recognition accuracy ≥5mil
Main Display	Dimension: 10.1inch Resolution: 800*1280 Type: TFT-LCD Luminance: 230 CD/M ² Interface: MIPI		Reading angle: 35° horizontally and 27° vertically along the scanning light
Touch screen	Dimension: 10.1inch Type: Capacitive		Reading code: 1D: Code 128, EAN-13, EAN-8, UPC-E, UPC-A, ISBN, ISSN, Code11, ITF-25 (Interleaved 2 of 5), Code39, Code93, Code32, Codabar, Matrix 2 of 5, Industrial 25, IATA 25, MSI Plessey 2D: QR Code, Micro QR, Data Matrix, PDF417
Scanner module 1 (Optional)	Prompt mode: buzzer, LED indicator Trigger mode: command trigger, automatic induction trigger, continuous trigger Setting method: scan code setting, command setting Communication interface: USB HID keyboard Recognition angle: rotation 360°, left and right tilt ±45°, front and back tilt ±45°, recognition accuracy ≥5mil Reading code: 1D: Code128, Code39, EAN, UPC, Code93, ISBN-13, Interleaved 2 of 5 2D: QR Code	Port	Power port: 1x RJ12: 6P6C cash drawer port 1x RJ11: 6P4C com port 1x USB 2.0 TypeA: 4x RJ45 LAN: 1x TF: 1x SIM: 1x(optional) 3.5mm Headphone jack: 1x
Internet	WIFI: Network standard: IEEE 802.11b/g/n Bluetooth: BT2.1+EDR/3.0/4.0/4.1/4.2 BLE Ethernet: 10/100M adaptive	Dimension	169x157.3x310.3mm (LxWxH) (Without camera)
Power adapter	12V 3A	Weight	Net weight: 1.2kg Gross weight: 1.9kg
Voice prompt	Built-in 2W speaker	Environment	Working temperature: -10°C-40°C Storage temperature: -20°C-55°C Humidity: 20%-90% RH



GUANGZHOU ZONERICH BUSINESS MACHINE CO., LTD.

Add : Zonerich Science Park, North Gate, No.17, YunJun Rd., Luo Gang District, Guangzhou, China
Tel : +86-20-66671666 Fax : +86-20-66600577 E-mail : trade@zonerich.com