

Touch POS System

ZQ-T9150

ZQ-T9120

HIGHLIGHTS

- Housing made by aluminum
- Fan and Fanless system optional
- True flat water proof touch screen
- Easy to maintenance, Just loose three screws if change RAM and SSD
- Various options of peripherals

Optional

- Customer display 2X20VFD
- MSR, I-Button, RFID



SPECIFICATIONS

Model	ZQ-T9150 with fan	ZQ-T9120/ZQ-T9150 fanless
CPU	Intel® Celeron® Processor 1037U	Intel® Atom™ Processor D2550
Memory	1 x DDR3 2GB	1 x DDR3 2GB
Network	RTL8168DE PCI-E Gigabit Ethernet NIC	RTL8168DE PCI-E Gigabit Ethernet NIC
Power Supply	100-240V/ 3.5A 47~63Hz	100-240V/ 3.5A 47~63Hz
Video Card	Intel Graphics Media	Intel Graphics Media
Sound Card	Accelerator3150(256MB/Intel)RTL ALC662 @INTEL 82801G(ICH7)High Definition Audio	Accelerator3150(256MB/Intel) RTL ALC662 @INTEL 82801G(ICH7)High Definition Audio
Dimension	350x200x330mm(WxDxH)	ZQ-T9120:290X200X310mm ZQ-T9150:350x200x330mm(WxDxH)
O.S. Compliant	Windows XP / VISTA/WIN7/WIN8(opotional)	Windows XP / VISTA/WIN7/WIN8(opotional)
HDD	M-SATA 32 G	M-SATA 32 G
I/O PORTS		
USB	4 x USB 2.0 port	4 x USB 2.0 port
Serial Port	2 x DB-9 RS232	3 x DB-9 RS232
LAN	1 x 10/100/1000 Mbps	1 x 10/100/1000 Mbps
Audio	Interface x 2	Interface x 1
VGA	1 x DB-15 VGA Interface	1 x DB-15 VGA Interface
HDMI	1 x HDMI	N/A
DISPLAY		
Viewing Angle	85 degree adjustable	85 degree adjustable
LCD	15" TFT LCD	ZQ-T9120:12" TFT LCD ZQ-T9150:15" TFT LCD
Max. Resolution	1024 x 768	1024 x 768
Touch Screen	5-wires resistive 20,000,000 times touch life (P-CAP multi-touch optional)	5-wires resistive 20,000,000 times touch life (P-CAP multi-touch optional)
ENVIRONMENT		
Operation Temperature	0~40℃	0~40℃
Storage Temperature	-40~50℃	-40~50℃
Humidity	38~80%℃	38~80%℃



Optional MSR



Aluminum housing



Optional I-button



Various interfaces